

## 5

## Filtros de gasoil

FILTROS CON CAZOLETA **RACOR**.

Ref	Flujo	Elemento	Rosca cabeza	Peso	Caída de presión	Presión máx.	Altura máx.	A (mm)	B (mm)	C (mm)
RAC500MA30	227 l/h 60 gph	2010	1/4-18 NPTF	2 kg	0.61 PSI 0.04 bar	15 PSI 1 bar	102 mm	292	147	122
RAC900VMA30	340 l/h 90 gph	2010		4,9 kg	0.30 PSI 0.021 bar		127 mm	432	152	178
RAC900MA30	341 l/h 90 gph	2040		3 kg	0.34 PSI 0.02 bar		127 mm	432	152	178
REC1000VMA30	681 l/h 180 gph	2010		5,6 kg	0.43 PSI 0.03 bar		254 mm	557	220	200
RAC1000MA30	681 l/h 180 gph	2020		5 kg	0.49 PSI 0.03 bar		254 mm	559	152	178
RAC75/500MAX	454 l/h 120 gph	2010		7,7 kg	0.70 PSI 0.05 bar		102 mm	292	368	241
RAC75/1000MA30	681 / 1363 l/h 180 / 360 gph	2020		13,6 kg	3.70 PSI 0.25 bar		254 mm	559	476	279

## ELEMENTOS DE RECAMBIO ➤

Ref. para 500	Ref. para 900	Ref. para 1000	Micras	Color
RAC2010SM-OR	RAC2040SM-OR	RAC2020SM-OR	2	Marrón
RAC2010TM-OR	RAC2040TM-OR	RAC2020TM-OR	10	Azul
RAC2010PM-OR	RAC2040PM-OR	RAC2020PM-OR	30	Rojo

↓  
S: SECUNDARIO  
T: PRIMARIO O SECUNDARIO/FINAL  
P: PRIMARIO

**RACOR**

Ref. para 500	Ref. para 900	Ref. para 1000	Micras
REC3581760	REC889419	REC889422	30

**RECMAR**